

## Your Testing Specialist



## UTI720E

## Enhanced Thermal Imager

UTi720E is an advanced thermal imager with Wi-Fi capability. Its large 3.5" IPS screen can clearly display 256x192 thermal resolution, 2MP visual camera, or a blended image of both. UTi720E's detachable battery pack is also convenient for easy and quick battery change, allowing continuously work for long periods of time.









resolution	256x192 pixels
Display	3.5" IPS (640x480 pixels)
ield of view (FOV)	56" (H) x 42.2" (V)
Thermal sensitivity (NETD)	50mK
patial resolution (IFOV)	3.8mrad
rame rate	25Hz
emperature measurement range	-20°C ~ 550°C (-4°F ~ 1022°F)
Accuracy	±2°C or ±2% whichever is greater
Battery	Li-ion battery (3.7V 5200mAh)
Battery operating time	Continuous operating time ≥4h
Function	
Palettes	7 (White hot, Black hot, Red hot, Ironbow, Rainbow HC, Rainbow, Lava)
Digital zoom	2x, 4x
mage modes	Thermal, Visual Image, Fusion, PIP
sotherm	6 (Auto, Ratio, Below, Above, Section, Manual)
.ED flashlight	Dual LED flashlight
V i-Fi download photos with mobile APP	٧
Auto tracking for Lo/Hi temperature	₹
Alarm	v (Icon/Flashlight)
Storage	16GB Micro SD Card
On screen temperature analysis tools	Point 5/Line 1/Area 6
missivity	0.95 default (0.01~1.00 adjustable)
oftware	Analysis, Real-time display
Protection	IP54/2m
Certificates	CE, UKCA, FCC, RoHS
JSB	Type-C
Package	
Product net size	260mm x 97mm x 99mm
Product net weight	630g
itandard accessories	Micro SD card, Type-C USB cable, English manual, Li-ion battery pack